



CONCRETE IMPREGNATOR

Concrete Treatment Solution



FEATURES

- Protection from aqueous solutions and organic liquids
- Increases concrete durability
- Economical
- Ready to use

AREAS OF USE

Concrete surfaces

DESCRIPTION

CONCRETE IMPREGNATOR is a solution used as a sealant in cement and concrete industries to build chemical and physical durability of concrete surfaces, such as walls, warehouse floors, bridges, storage tanks and many others where concrete is used as a building structural material.

DIRECTIONS FOR USE

Apply with a brush or using a suitable applicator. Continue to apply to the surface until no more product is absorbed. Allow to dry for a minimum period of 10 hours preferably overnight. 1L of solution covers approximately 5m².

Consult your Jasol representative for further information.

SAFETY INFORMATION

CONCRETE IMPREGNATOR is classified as Hazardous according to the GHS.

CONCRETE IMPREGNATOR is NOT classified as Dangerous Goods according to the ADG Code

CONCRETE IMPREGNATOR is classified as a Scheduled Poison according to the SUSMP.

Avoid contact with eyes and skin. Refer to SDS for further information.

FIRST AID INFORMATION

For advice in an emergency, contact Poisons Information Centre (Phone Australia 13 11 26) or a doctor at once. If swallowed do NOT induce vomiting. Wash mouth thoroughly with water and seek medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

PHYSICAL & CHEMICAL PROPERTIES

Customer Service: 1800 334 679 jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

APPEARANCE Clear to Slightly Hazy Liquid COLOUR Colourless

ODOUR Odourless 11.5-12.5 SPECIFIC GRAVITY

FLAMMABILITY Not Flammable









Providing hygiene service solutions since 1934

Revision: 2.0 Page 1