



JAFLOC AE49

Polymer Flocculant

FEATURES

- Water conditioning
- Compatible with mineral coagulants
- Removal of colloidal material

AREAS OF USE

- Industrial water treatment
- Waste water treatment
- Municipal water treatment

DESCRIPTION

JAFLOC AE49 is a polyacrylamide solution used for water treatment in various industries.

DIRECTIONS FOR USE

The dose rate of JAFLOC AE49 will depend upon a number of factors. For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

JAFLOC AE49 is NOT classified as Hazardous according to the GHS.
 JAFLOC AE49 is NOT classified as Dangerous Goods according to the ADG Code (7th Ed).
 JAFLOC AE49 is NOT a Scheduled Poison according to the SUSMP.

FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26)** or **a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**
jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM	Viscous Liquid
COLOUR	Milky
pH	5.0 – 8.0
IONIC CHARACTER	Anionic
CHARGE DENSITY	Medium
MOLECULAR WEIGHT	High
SPECIFIC GRAVITY	1.00 – 1.10
Av. NON-VOLATILE SOLIDS	34 - 41%
BULK VISCOSITY	500 - 2000 cps
MAX. CONCENTRATION	10g/L
STABILITY OF D.I. SOLUTIONS	8 Days
Approx. BULK DENSITY @ 5g/L	2400 cps
STORAGE TEMPERATURE	5-35°C (5-30°C inside building)
SHELF LIFE	6 months



2144090

