

# JAFLOC CP29

## Polymer Flocculant



### FEATURES

- Easy to use
- Compact size
- Short reaction time

### AREAS OF USE

- Water purification
- Waste water treatment
- Raw water treatment

### DESCRIPTION

JAFLOC CP29 is a water purification powder designed to be used in the physico-chemical water purification process after the coagulation step. It can be used in various industrial sectors, such as mining, paper milling, oil industry, municipal wastewater and others.

### DIRECTIONS FOR USE

The dosage rate and the mixing speed and time for JAFLOC CP29 will depend upon a number of factors, including the type, composition and volume of the system being treated. For assessment before use, please consult your Jasol representative.

### SAFETY INFORMATION

JAFLOC CP29 is NOT classified as Hazardous according to the GHS.  
JAFLOC CP29 is NOT classified as Dangerous Goods according to the ADG Code (7<sup>th</sup> Ed).  
JAFLOC CP29 is NOT a Scheduled Poison according to the SUSMP.

#### FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26) or a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

**24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953**

### PRODUCT ENQUIRIES

Customer Service: **1800 334 679**

[jasolcsteam@gwf.com.au](mailto:jasolcsteam@gwf.com.au)

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

### PHYSICAL & CHEMICAL PROPERTIES

<b>FORM</b>	Granular Powder
<b>COLOUR</b>	White
<b>CHARGE DENSITY</b>	Low
<b>pH</b>	2.5-4.5 (5 g/L)
<b>RELATIVE DENSITY</b>	0.6-0.9
<b>MOLECULAR WEIGHT</b>	Very High
<b>MELTING POINT</b>	>100°C

15kg

2144100

