



# JAFLOC LBCESC79

## Polymer Flocculant

### FEATURES

- Water conditioning
- Compatible with mineral coagulants
- Removal of colloidal material

### AREAS OF USE

- Industrial water treatment
- Waste water treatment
- Municipal water treatment

### DESCRIPTION

JAFLOC LBCESC79 is a very high density charge polyacrylamide solution used for waste water flocculation in various industries.

### DIRECTIONS FOR USE

The dose rate of JAFLOC LBCESC79 will depend upon a number of factors. For assessment before use, please consult your Jasol representative.

### SAFETY INFORMATION

JAFLOC LBCESC79 is NOT classified as Hazardous according to the GHS.  
 JAFLOC LBCESC79 is NOT classified as Dangerous Goods according to the ADG Code (7<sup>th</sup> Ed).  
 JAFLOC LBCESC79 is NOT a Scheduled Poison according to the SUSMP.

#### FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26)** or **a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

**24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953**

### PRODUCT ENQUIRIES

Customer Service: **1800 334 679**  
[jasolcsteam@gwf.com.au](mailto:jasolcsteam@gwf.com.au)

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

### PHYSICAL & CHEMICAL PROPERTIES

<b>FORM</b>	Opaque Liquid
<b>COLOUR</b>	Milky
<b>pH</b>	4.0-6.0 (@5g/L)
<b>IONIC CHARACTER</b>	Cationic
<b>CHARGE DENSITY</b>	Very High
<b>MOLECULAR WEIGHT</b>	High
<b>SPECIFIC GRAVITY</b>	1.05
<b>Av NON-VOLATILE SOLIDS</b>	50%
<b>BULK VISCOSITY</b>	1200 cps
<b>MAX. CONCENTRATION</b>	5g/L
<b>STABILITY OF D.I. SOLUTIONS</b>	1 day
<b>DILUTION TO OBTAIN 5g/L</b>	90
<b>STORAGE TEMPERATURE</b>	0-35°C



