

JAPAC 23

Coagulant



FEATURES

- Enhanced floc formation capacity
- Rapid chemical reaction response

AREAS OF USE

- Waste water treatment

DESCRIPTION

JAPAC 23 is a polyaluminium hydroxychloride coagulant used for waste water treatment operations. It has around 3 times as much active ingredient as liquid alum. It is a cost effective solution that facilitates the formation of flocs which are removed during the subsequent clarification or filtration stages.

DIRECTIONS FOR USE

The dose rate of JAPAC 23 will depend upon a number of factors, such as the composition and pH of waste water system.

For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

JAPAC 23 is classified as Hazardous according to the GHS.
 JAPAC 23 is NOT classified as Dangerous Goods according to the ADG Code (7th Ed).
 JAPAC 23 is NOT a Scheduled Poison according to the SUSMP.
 Avoid contact with eyes and skin. Refer to SDS for further information.

FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre (Phone Australia 13 11 26) or a doctor at once**. If swallowed do NOT induce vomiting. Wash mouth thoroughly with water and seek medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**
jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM	Clear to Hazy Liquid
COLOUR	Light Yellow
ODOUR	Mild Odour
pH	2.5-3.5
SPECIFIC GRAVITY	1.20 at 20°C
FLAMMABILITY	Not Flammable

